



## trivum SCW165

trivum speaker for ceiling and wall mounting was developed in order to achieve the highest possible efficiency factor combined with the clearest audio reproduction. Distortions and sound colorations are reduced to an absolute minimum resulting in a clear intelligibility.

The SCW series are available in two versions: mono (SCW165) and stereo (SCW165-S). The SCW speaker has a significantly reduced installation depth of only 80 mm.

They are the perfect complement to the trivum multiroom systems.



### Power

The SCW165 has a high, short-term peak power capacity of 160 watt.



### Efficiency factor

With its efficiency factor of 92 dB/W the SCW165 belongs to the market leaders in this size.



### Impedance

A high impedance of 8 ohm is very important for flush mount speakers since they are usually connected to long cables.



### Tweeter Level

The SCW165 has a tweeter level adjustment in order to adjust the sound to spacial and acoustical prerequisites.



### Reproduction quality

The loudspeakers impress with clear reproduction and audibility due to the minimization of distortions and sound intelligibility.



### Grills

The included round and square grills can be exchanged anytime without the need to remove or exchange the speakers.



### Installation

Fast and easy installation in 3 steps:

- Cut out mounting hole
- Install cable and speaker
- Install the grill

**Function**

Speaker for ceiling and wall mounting.

**Technical Data**

Tweeter diameter	25 mm silk dome
Tweeter mounting	-
Tweeter level switch	yes, 0 dB & -3 dB
Woofer diameter	165 mm
Impedance	8 Ω
Power capacity (peak)	160 W
Sensitivity	92 dB/W
Response -3 dB	58 Hz–21 kHz

**Grills**

Round grill (diameter)	233 mm
Square grill	232 x 232 mm
Magnetic grill fixing	yes

**Dimensions**

$t_1$	2 mm
$d_1$	224 mm
Ultra thin bezel	1 mm
Ultra shallow grill	3.5 mm
Installation depth ( $t_2$ )	80 mm
Mounting diameter ( $d_2$ )	202 mm
Net weight	1620 g

**Frequency response**

